

vManage

=====

```
conf t
vpn 0
no int eth0
exit
commit
```

```
system
system-ip 200.0.0.1
host-name vManage
organization-name Sysable
vbond 20.1.1.3
site-id 100
exit
commit
```

```
vpn 0
int eth1
ip add 20.1.1.1/24
no shutdown
tunnel-interface
allow-service all
allow-service netconf
allow-service sshd
exit
exit
ip route 0.0.0.0/0 20.1.1.254
exit
```

```
vpn 512
int eth0
ip add 192.168.145.4/24
no shutdown
exit
exit
```

```
commit
```

=====

vBond

=====

```
conf t
```

```
system
system-ip 200.0.0.3
host-name vBond
organization-name Sysable
vbond 20.1.1.3 local
site-id 100
exit
commit
```

```
vpn 0
int ge0/0
ip add 20.1.1.3/24
no shutdown
tunnel-interface
encapsulation ipsec
allow-service all
allow-service netconf
allow-service sshd
exit
exit
ip route 0.0.0.0/0 20.1.1.254
exit
```

```
vpn 512
int eth0
ip add 192.168.145.3/24
no shutdown
exit
exit
commit
```

```
=====
vSmart
```

```
=====
```

```
conf t
vpn 0
no int eth0
exit
commit
```

```
system
system-ip 200.0.0.2
host-name vSmart
organization-name Sysable
vbond 20.1.1.3
site-id 100
clock timezone Asia/Kolkata
exit
```

```
vpn 0
int eth1
ip add 20.1.1.2/24
no shutdown
tunnel-interface
allow-service all
allow-service netconf
allow-service sshd
exit
exit
ip route 0.0.0.0/0 20.1.1.254
exit
```

```
vpn 512
int eth0
ip add 192.168.145.2/24
no shutdown
exit
exit
```

```
commit
```

```
=====
R1:Edge Router
```

```
=====
conf t
int e0/0
ip add 20.1.1.254 255.255.255.0
no sh
int e0/1
ip add 172.16.2.254 255.255.255.0
no sh
int e0/2
ip add 172.16.3.254 255.255.255.0
no sh
exit
```

```
do wr
```

```
=====
BR1-Vedge
```

```
conf t
system
system-ip 100.1.1.1
host-name BR1
organization-name Sysable
vbond 20.1.1.3
site-id 1
exit
```

```
vpn 0
int ge0/1
ip add 172.16.3.1/24
no shutdown
tunnel-interface color mpls
encapsulation ipsec
allow-service all
allow-service netconf
allow-service sshd
exit
exit
```

```
int ge0/0
ip add 172.16.2.1/24
no shutdown
tunnel-interface color biz-internet
```

```
encapsulation ipsec
allow-service all
allow-service netconf
allow-service sshd
exit
exit
ip route 0.0.0.0/0 172.16.2.254
ip route 0.0.0.0/0 172.16.3.254
exit
```

```
vpn 512
int eth0
ip add 192.168.145.11/24
no shutdown
exit
exit
commit
```

```
vshell
BR1:~$ scp admin@20.1.1.1:/home/admin/rootca.crt .
.exit
```

```
BR1# request root-cert-chain install /home/admin/rootca.crt
```

```
BR1# request vedge-cloud activate
chassis-number 62EFC7DE-7F33-4A97-1B37-9C61DA679FCF
token 4fc597e9e00ea54898bcfe2fa3408d79
```

```
BR1# request vedge-cloud activate chassis-number enterchassisnumber token serialnumber
=====
==
DC-1
conf t
system
system-ip 100.1.1.3
host-name DC-1
organization-name Sysable
vbond 20.1.1.3
site-id 3
exit
```

```
vpn 0
int ge0/0
ip add 172.16.2.3/24
no shutdown
tunnel-interface color biz-internet
encapsulation ipsec
allow-service all
allow-service netconf
allow-service sshd
ip route 0.0.0.0/0 172.16.2.254
exit
exi
commit
```

```
vpn 512
int eth0
ip add 192.168.145.15/24
no shutdown
exit
exit
commit
```

```
vshell
BR1:~$ scp admin@20.1.1.1:/home/admin/rootca.crt .
exit
BR1# request root-cert-chain install /home/admin/rootca.crt
!BR1# request vedge-cloud activate chassis-number
62EFC7DE-7F33-4A97-1B37-9C61DA679FCF token !4fc597e9e00ea54898bcfe2fa3408d79
BR1# request vedge-cloud activate chassis-number enterchassisnumber token serialnumber
```

```
=====
=====
```

```
DC-2
conf t
system
system-ip 100.1.1.4
host-name DC-2
organization-name Sysable
vbond 20.1.1.3
site-id 3
exit
```

```
vpn 0
int ge0/0
ip add 172.16.3.3/24
no shutdown
tunnel-interface color mpls
encapsulation ipsec
allow-service all
allow-service netconf
allow-service sshd
ip route 0.0.0.0/0 172.16.3.254
exit
exi
```

```
commit
```

```
vpn 512
int eth0
ip add 192.168.145.16/24
no shutdown
exit
exit
commit
```

```
vshell
```

```
BR1:~$ scp admin@20.1.1.1:/home/admin/rootca.crt .
exit
BR1# request root-cert-chain install /home/admin/ROOTCA.crt
!BR1# request vedge-cloud activate chassis-number
62EFC7DE-7F33-4A97-1B37-9C61DA679FCF token !4fc597e9e00ea54898bcfe2fa3408d79
BR1# request vedge-cloud activate chassis-number enterchassisnumber token serialnumber
=====
```